

G 8066
G 8072

Products

Dishwashers

Key Features

Tank wash system: High throughput performance making it ideal for busy kitchens in hotels and schools.

Triple filter: Provides high hygiene level for extended tank operation.

Clear visual operating display: Easy to operate controls with colour coding on G 8072.

Wide range of baskets and tabling: Flexible and versatile solutions to suit most applications.

Option of liquid detergent feed: Eliminates potential hazard associated with manual dosing.

G 8066



G 8072



Design

Freestanding	x	x
Single basket chamber	x	x
Basket size: 500 mm x 500 mm	o	o

Controls

Touch control panel	x	x
---------------------	---	---

Programmes

Number of programmes	3	3
Duration (secs)	90 / 120 / 180	60 / 120 / 180
Self-cleaning programme	x	x

Tank

Capacity (litres)	17	45
Heating (kW)	0.75	1.8
Wash temperature °C (factory default)	65	65

Boiler

Capacity (litres)	6	12
Heating (kW)	9.25	9
Rinse temperature °C (factory default)	Wash temp. + 20°C	85

x Standard feature o Optional feature - Feature not available

Products

Dishwashers

G 8066

G 8072

Dispenser systems

Internal pump for rinse aid	x	x
Internal reservoir for rinse aid	o	-
Internal pump for detergent	o	o
Internal reservoir for detergent	o	-
Socket connection for external liquid dispensing pump	x	x
G 60 external liquid dispensing pump	o	o

Water softener

Built-in, up to 25°dH	-	o
Built-in, up to 30°dH	o	-

Circulation pump

Throughput [l/min]	400	800
--------------------	-----	-----

Plumbing

1 x cold/hot water 1/2" with 3/4" threaded union (max 65°C)	x	x
Built-in rinse booster pump	x	x
Inlet pressure 100 - 1000 kPA	x	-
Inlet pressure 80 - 600 kPA	-	x
Drain pump	x	x
Maximum head	1 m	0.65 m

Electrical connection

1N AC 220-240 V 50 Hz with cable	6.4 kW / 1 x 32A	-
1N AC 220-240 V 50 Hz with cable (load interlocked)	-	7.7 kW / 1 x 32A
3N AC 400 V 50 Hz with cable (load unlocked)	10.5 kW / 3 x 16 A	9.5 kW / 3 x 16A
3N AC 400 V 50 Hz with cable (load interlocked)	-	10.7 kW / 3 x 16A

Dimensions, weight

Height without lid/including optional lid (mm)	820 / 850	-
Height hood lowered/hood raised (mm)	-	1470 / 1940
Width x depth (mm)	598 x 600	800 x 880
Net weight [kg]	70	118

External casing

Stainless steel	x	x
DET 60/1 stainless steel lid	o	-

Sound levels (IEC 704-1 and 704-2-4)

Noise level	60.2 dB	75.1 dB
-------------	---------	---------

x Standard feature o Optional feature - Feature not available

Miele Professional preserves the right to change the machines and specification at anytime, without any prior notice. All information printed is only for information and never legally binding.

