

Products

13-16 Kg Tumble Dryers

Key Features



Powerplus: A performance that offers more with powerful heater elements for fast heat-up and short cycles. Large drum volume for high laundry loads and intelligent solutions for reliable results - Professional, commercial technology.

Careplus: The patented honeycomb drum ensures laundry is cared for - air pockets provide cushion protection and reduce fibre wear. SoftLift ribs ensure traction is increased, this ensures that the laundry travels further and has extended exposure to the heated air flow.

Flexplus: Profitronic B Plus Controls have 10 fixed and 2 time controlled programmes as well as the “Low temperature” function that covers the range of moisture controlled applications. Profitronic M controls - Freely programmable. Standard programme packages and a total of 199 programme slots. The graphic display combines symbols and text for easy programming and programmes are selected via a rotary dial. The temperatures, holding times, wash times, drum rhythms, spin speeds and dosing are all programmable to suit your needs. Chip card reader fitted as standard.

Ecoplus: A sustainable, cost-effective performance, achieving optimum results. Robust design using recyclable materials for sustainability. Hot air recycling combined with a reverse action drum to ensure maximum energy efficiency.

Comfortplus: A simple, user-friendly solution when selecting programmes by using rotary switch and pushbuttons. With a large drum opening for simple loading and unloading.

	PT 8333	PT 8337
		
Design		
Frontloader, door opening [Ø mm]	520	520
Suitable for stacking	-	-
Drying system		
Vented with AirRecycling system	x	x
Air inlet and exhaust outlet diameter [mm]	DN 150	DN 150
Capacity		
Max. load 1:25 - 1:20 [kg]	13 - 16	13 - 16
Patented Honeycomb drum volume [litres]	250	400
Controls		
PROFITRONIC M	-	x
PROFITRONIC B PLUS	x	-
Slot for communication module	x	x

*Electro zinc plated x Standard feature o Optional feature - Feature not available

Products

13-16 Kg Tumble Dryers

	PT 8333	PT 8337
Connection options		
Communication module with serial interface	o	o
Payment system	o	-
Peak load cut-out	o	o
Heating		
Electric (EL), Gas (G), Steam (D)	EL/G	EL/G
Electrical connection (electric heating)		
3N AC 380-415 V 50 Hz	14.3 kW/3 x 25 A	23.8 kW/3 x 50 A
3 AC 440 V 60 Hz	14.3 kW/3 x 25 A	23.8 kW/3 x 50 A
Electrical connection (gas heating)		
1N AC 220-240 V 50 Hz	0.8 kW/1 x 10 A	-
3N AC 380-415 V 50 Hz	-	1.3 kW/3 x 10 A
Dimensions, weight (electric heating)		
External dimensions H/W/D [mm]	1400/906/836	1400/906/1148
Net weight [kg]	148	191
External finish		
Front, sides and lid octoblué, rear panel*	x	x
Front stainless steel, lid and sides octoblué, rear panel*	o	o
Sound levels (IEC 704-1 and 704-2-4)		
	68.6 dB (A)	72.8 dB (A)
Floor load		
Maximum floor load in operation (EL/G)	1636 N/1651 N	2163 N/2143 N
Maximum floor load in operation (STEAM)	-	2408 N
Frequency	-	-

*Electro zinc plated x Standard feature o Optional feature - Feature not available

Miele Professional preserves the right to change the machines and specification at anytime, without any prior notice. All information printed is only for information and never legally binding.

